

WHAT IS CLAIMED IS:

1. A liquid crystal display device comprising:
- a first substrate;
 - a second substrate;
 - a liquid crystal layer between the first and second substrates;
 - a plurality of gate lines and data lines on the first substrate to define pixel regions;
 - a common auxiliary electrode on the first substrate to surround the pixel regions;
 - a pixel electrode having at least one or more electric field induction windows on the first substrates; and
 - at least one or more dielectric structures on the common electrode.
2. The device of claim 1, wherein the common auxiliary electrode is on a layer equal to the gate lines.
-
3. The device of claim 1, wherein the dielectric structures extend from the second substrate to the first substrate.

4. The device of claim 2, wherein the dielectric structures act as a spacer between the first and second substrates.

5. The device of claim 1, wherein each of the pixel regions is divided into one or more sections to form a multi-domain pixel.

6. The device of claim 5, wherein the one or more sections of the pixel regions have different driving characteristics.

7. The device of claim 1, further comprising a common auxiliary electrode formed in the electric field induction windows.

8. The device of claim 1, wherein the electric field windows include slits.

9. The device of claim 1, wherein the common auxiliary electrode partially overlaps the pixel electrode.

10. The device of claim 1, further comprising an alignment film on at least one of the first

and second substrates.

11. The device of claim 1, further comprising a phase difference film on at least one of the first and second substrates.

Sub
AZ
encl

12. A liquid crystal display device comprising:

- a first substrate;
- a second substrate;
- a liquid crystal layer between the first and second substrates;
- a plurality of gate lines and data lines on the first to define pixel regions;
- a common auxiliary electrode on the first substrate to surround the pixel regions;
- a pixel electrode having at least one or more electric field induction windows on the first substrate; and
- at least one or more dielectric structures on the pixel electrode.

13. The device of claim 12, wherein the common auxiliary electrode is on a layer equal to the gate lines.

14. The device of claim 12, wherein the dielectric structures extend from the first substrate to the second substrate.

15. The device of claim 14, wherein the dielectric structures act as a spacer between the first and second substrates.

16. The device of claim 12, wherein each of the pixels is divided into one or more sections to form a multi-domain pixel.

17. The device of claim 16, wherein the one or more sections of the pixel regions have different driving characteristics.

18. The device of claim 12, further comprising a common auxiliary electrode formed in the electric field induction windows.

19. The device of claim 12, wherein the electric field induction windows include slits.

20. The device of claim 12, wherein the common auxiliary electrode partially overlaps the pixel electrode.

21. The device of claim 12, further comprising an alignment film on at least one of the first and second substrates.

22. The device of claim 12, further comprising a phase difference film on at least one of the first and second substrates.

Sub
A3
end

11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51 52 53 54 55 56 57 58 59 60 61 62 63 64 65 66 67 68 69 70 71 72 73 74 75 76 77 78 79 80 81 82 83 84 85 86 87 88 89 90 91 92 93 94 95 96 97 98 99 100